



2.0 to 18.0GHz -16 Way Power Divider/Splitter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.

RF Characteristics

Model Number	Freq.Range (GHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Input Max	VSWR Output Max	Phase Unbalance	Amplitude Unbalance	Pow Splitter	er (W) Combiner	Connector Type	Temp.(°C)
UIY16PD215120A 2T18SF	2.0 ~ 18.0	5.8 (Split 12dB)	15	2.0	1.5	±20°	±1.5dB	10	3	SMA-F	-55 ~ +85

- Listed are specific frequency ranges and other ranges are available by custom.
 - Please provide the below information when inquiring and mark * is required.
 - * 1. The specific frequency ranges.
 - 2. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China. Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959

Web: www.uiyinc.com E-mail: sales@uiyinc.com