



18 to 40GHz - 4 Way Power Divider/Splitter

Design Features


- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.

RF Characteristics

Model Number	Freq.Range (GHz)	Insertion Loss Max(dB)	Ripple Max(dB)	Isolation Min(dB)	VSWR Input Max	Phase Unbalance	Amplitude Unbalance	Power (W)		Connector	- (0)
								Forward	Reverse	Туре	Temp.(°C)
UIY4PD5230A 18T40KF	18.0~40.0	1.8 (Split 6dB)	1.0	15.0	1.9	±8°	±0.6dB	10	1	2.92-F	-40~+80

- Listed are specific frequency ranges and other ranges are available by custom.
 - Please provide the below information when inquiring and mark * is required.
 - * 1. The specific frequency ranges.
 - 2. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5

Web: www.uiyinc.com

E-mail: sales@uiyinc.com

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China. Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959