

## 300 to 475MHz – Coaxial Isolator

### Design Features


- ◆ Can be dual junction or multiple for high isolation.
- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

### RF Characteristics

Model Number	Freq. Range (MHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYBCI6060H300T475SF	300 ~ 475	0.8	18	1.3	100	50	SMA-F	25±5
		1.0	17	1.35				-40 ~ +85
UIYBCI6060H300T475NF	300 ~ 475	0.8	18	1.3	100	50	N-F	25±5
		1.0	17	1.35				-40 ~ +85

- <sup>2</sup> Listed are specific frequency ranges and tailor-made ranges are available.
- <sup>2</sup> Please provide the information below when inquiring and mark \* is required.
- \* 1. The specific frequency ranges
  - \* 2. Power handling (Forward, Reverse, Peak, etc.)
  - \* 3. Connect type (SMA Male/ Female, N Male/ Female, etc.)
  - 4. Other special request if have (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

### Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5