



23 to 28GHz - Band Pass Filter

Design Features


- ♦ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- Custom design available upon request.
- Support one year standard warranty.

RF Characteristics

	Model Number	Pass Band (GHz)	Insertion Loss Max(dB)	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
U	JIYBPF3514B23T28KF	23.0 ~ 28.0	2.0	1.8	70dB@DC~16.5GHz 70dB@34.5~40.0GHz	10	2.92mm-F	-40 ~ +7 0

- ² Listed are specific frequency ranges and other tailor-made ranges are available.
- ² Please provide the below information when inquiring and mark * is required.
 - * 1. The specific pass band frequency range.
 - * 2. The specific rejection and frequency.
 - 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.0

 No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China.
 Web: www.uiyinc.com

 Tel: +86-755-83748888
 +86-755-25999990
 Fax: +86-755-25999959
 E-mail: sales@uiyinc.com