



13700 to 14550MHz - Band Pass Filter

Design Features


- ♦ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.
- Military, space and commercial applications.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Pass Band (MHz)	Insertion Loss Max(dB)	Ripple (dB)	VSWR Max	Rejection	Power (W)	Connector Type	Temp.(°C)
UIYBPF8717A13700T14550SFTSM	13700 ~ 14550	1.5	±0.8	1.5	30dB @14700MHz 80dB @12800MHz	10	SMA-F to SMA-M	-40 ~ +85
UIYBPF8717A13700T14550SF	13700 ~ 14550	1.5	±0.8	1.5	30dB @14700MHz 80dB @12800MHz	10	SMA-F	-40 ~ +85

- Listed are specific frequency ranges and tailor-made ranges are available.
- ² Please provide the below information when inquiring and mark * is required.
 - * 1. The specific pass band frequency range
 - * 2. The specific rejection and frequency
 - 3. Other special requests (such as Insertion Loss, VSWR, Connector Type, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.1

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China. Tel: +86-755-83748888 +86-755-25999990 Fax: +86-755-25999959

Web: www.uiyinc.com
E-mail: sales@uiyinc.com