

25W 18GHz N – Coaxial Attenuator

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics



Model Number	Freq. Range	Power	Attenuation Value	Attenuation Tolerance	VSWR Max	Connector Type	Impedance
UIYCA25AN8A3	DC-8GHz	25W	3 dB	±1.2 dB	1.3	N-M / N-F	50 Ω
UIYCA25AN8A6		25W	6 dB	±1.2 dB	1.3	N-M / N-F	50 Ω
UIYCA25AN8A10		25W	10 dB	±1.0 dB	1.3	N-M / N-F	50 Ω
UIYCA25AN8A20		25W	20 dB	±1.0 dB	1.3	N-M / N-F	50 Ω
UIYCA25AN8A30		25W	30 dB	±1.2 dB	1.3	N-M / N-F	50 Ω
UIYCA25AN8A40		25W	40 dB	±1.2 dB	1.3	N-M / N-F	50 Ω
UIYCA25AN124A3	DC-12.4GHz	25W	3 dB	±1.2 dB	1.35	N-M / N-F	50 Ω
UIYCA25AN124A6		25W	6 dB	±1.2 dB	1.35	N-M / N-F	50 Ω
UIYCA25AN124A10		25W	10 dB	±1.0 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN124A20		25W	20 dB	±1.0 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN124A30		25W	30 dB	±1.3 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN124A40		25W	40 dB	±1.3 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN18A3	DC-18GHz	25W	3 dB	±1.2 dB	1.35	N-M / N-F	50 Ω
UIYCA25AN18A6		25W	6 dB	±1.2 dB	1.35	N-M / N-F	50 Ω
UIYCA25AN18A10		25W	10 dB	±1.0 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN18A20		25W	20 dB	±1.0 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN18A30		25W	30 dB	±1.5 dB	1.4	N-M / N-F	50 Ω
UIYCA25AN18A40		25W	40 dB	±1.5 dB	1.4	N-M / N-F	50 Ω

² Listed are specific frequency ranges and tailor-made ranges are available.

² Please provide the information below when inquiring and mark * is required.

- * 1. Power handling, Attenuation Value
- 2. Connect type (SMA Male/ Female, N Male/ Female, etc.)
- 3. Other special requests (VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.1

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China.

Web: www.uiyinc.com

Tel: +86-755-83748888 +86-755-25999990

Fax: +86-755-25999959

E-mail: sales@uiyinc.com