

2W – N DC-3GHz Coaxial Attenuator

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Custom design available upon request.
- ◆ Military, space and commercial applications.
- ◆ Support one year standard warranty.

RF Characteristics


Model Number	Freq. Range	Power	Attenuation Value	Attenuation Tolerance	VSWR Max	Connector Type	Impedance
UIYCA2AN3A1	DC-3GHz	2W	1 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A2	DC-3GHz	2W	2 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A3	DC-3GHz	2W	3 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A5	DC-3GHz	2W	5 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A6	DC-3GHz	2W	6 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A10	DC-3GHz	2W	10 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A15	DC-3GHz	2W	15 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A20	DC-3GHz	2W	20 dB	±0.5 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A30	DC-3GHz	2W	30 dB	±0.6 dB	1.2	N-M / N-F	50 Ω
UIYCA2AN3A40	DC-3GHz	2W	40 dB	±1.5 dB	1.25	N-M / N-F	50 Ω
UIYCA2AN3A50	DC-3GHz	2W	50 dB	±1.5 dB	1.25	N-M / N-F	50 Ω
UIYCA2AN3A60	DC-3GHz	2W	60 dB	±1.8 dB	1.25	N-M / N-F	50 Ω

² Listed are specific frequency ranges and tailor-made ranges are available.

² Please provide the information below when inquiring and mark * is required.

- * 1. Power handling, Attenuation Value
- 2. Connect type (SMA Male/ Female, N Male/ Female, etc.)
- 3. Other special requests (VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is ±2% unless otherwise stated.

Ver. 5.2

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China.

Web: www.uiyinc.com

Tel: +86-755-83748888 +86-755-25999990

Fax: +86-755-25999959

E-mail: sales@uiyinc.com