

31 to 40GHz – Microstrip Isolator

Design Features

- ◆ Can be Dual Junction or Multiple for high isolation.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Freq. Range (GHz)	Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Forward Power(W)	Reverse Power(W)	Connector Type	Temp.(°C)
UIYMI34A31T39	31 ~ 39	1.0	14	1.4	2	2	Microstrip	-55 ~ +85
UIYMI34A31T40	31 ~ 40	1.2	14	1.5	2	2	Microstrip	-55 ~ +85
UIYMI34A32T38	32 ~ 38	1.0	14	1.4	2	2	Microstrip	-55 ~ +85
UIYMI34A32T40	32 ~ 40	1.0	14	1.4	2	2	Microstrip	-55 ~ +85
UIYMI34A33T37	33 ~ 37	1.0	14	1.4	2	2	Microstrip	-55 ~ +85
UIYMI34A35T40	35 ~ 40	1.0	14	1.4	2	2	Microstrip	-55 ~ +85

² Listed are specific frequency ranges and tailor-made ranges are available.


² Please provide the information below when inquiring and mark * is required.

* 1. The specific frequency ranges

* 2. Power handling (Forward, Reverse, Peak, etc.)

3. Other special requests (Insertion Loss, Isolation, VSWR, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5.2

No. 8, Lane 1, Xintun East Zone, Longgang District, Shenzhen 518172, China.

Tel: +86-755-83748888 +86-755-25999990

Fax: +86-755-25999959

Web: www.uiyinc.com

E-mail: sales@uiyinc.com