

850 to 3000MHz – Triplexer

Design Features

- ◆ High RF performance, ultra-competitive price.
- ◆ Military, space and commercial applications.
- ◆ Custom design available upon request.
- ◆ Support one year standard warranty.

RF Characteristics

Model Number	Freq. Range (MHz)		Insertion Loss Max(dB)	Isolation Min(dB)	VSWR Max	Power(W)	Connector Type	Temp.(°C)
UIYTX10086A850T3000NF	CH1	850 ~ 1000	0.5	30	1.22	100	N-F	-30 ~ +70
	CH2	1700 ~ 2000						
	CH3	2500 ~ 3000						
UIYTX10086A850T3000SF	CH1	850 ~ 1000	0.5	30	1.22	100	SMA-F	-30 ~ +70
	CH2	1700 ~ 2000						
	CH3	2500 ~ 3000						

² Listed are specific frequency ranges and tailor-made ranges are available.


² Please provide the information below when inquiring and mark * is required.

* 1. The specific frequency range TX and RX

* 2. Insertion Loss, Isolation, VSWR

3. Other special requests (Power handling, Temperature, Dimension, etc.)

Mechanical Drawing



Unit: mm/ inch, General part tolerance is $\pm 2\%$ unless otherwise stated.

Ver. 5